


# DIN25201 双叠自锁垫圈 规格表

DIN25201 dual-stacked self-locking washer


材质: sk5碳钢

表面处理: 达克罗涂层处理


规格	公制型号	美制型号	内径 $\phi i$	外径 $\phi o$	厚度 T	百件重 Kg/100pcs
NL3	M3	#5	3.4	7	1.8	0.03
NL3.5	M3.5	#6	3.9	7.6	1.8	0.04
NL3.5sp	M3.5	#6	3.9	9	1.8	0.06
NL4	M4	#8	4.4	7.6	1.8	0.04
NL4sp	M4	#8	4.4	9	1.8	0.06
NL5	M5	#10	5.4	9	1.8	0.05
NL5sp	M5	#10	5.4	10.8	1.8	0.11
NL6	M6		6.5	10.8	1.8	0.07
NL6sp	M6		6.5	13.5	2.5	0.2
NL1/4''		1/4''	7.2	11.5	2.5	0.08
NL1/4sp		1/4''	7.2	13.5	2.5	0.18
NL8	M8	5/16''	8.7	13.5	2.5	0.15
NL8sp	M8	5/16''	8.7	16.6	2.5	0.28
NL3/8''		3/8''	10.3	16.6	2.5	0.23
NL3/8sp		3/8''	10.3	21	2.5	0.48
NL10	M10		10.7	16.6	2.5	0.22
NL10sp	M10		10.7	21	2.5	0.47
NL11	M11	7/16''	11.4	18.5	2.5	0.29
NL12	M12		13	19.5	2.5	0.29
NL12sp	M12		13	25.4	3.4	0.93
NL1/2''		1/2''	13.5	19.5	2.5	0.27
NL1/2''sp		1/2''	13.5	25.4	3.4	0.9
NL14	M14	9/16''	15.2	23	3.4	0.56
NL14sp''	M14	9/16''	15.2	30.7	3.4	1.41
NL16	M16	5/8''	17	25.4	3.4	0.67
NL16sp''	M16	5/8''	17	30.7	3.4	1.28
NL18	M18		19.5	29	3.4	0.89
NL18sp''	M18		19.5	34.5	3.4	1.58
NL3/4		3/4''	20	30.7	3.4	1.05
NL3/4sp		3/4''	20	39	3.4	2.21
NL20	M20		21.4	30.7	3.4	0.93
NL20sp	M20		21.4	39	3.4	2.09
NL22	M22	7/8''	23.4	34.5	3.4	1.25
NL22sp	M22	7/8''	23.4	42	4.6	3.19
NL24	M24		25.3	39	3.4	1.74
NL24sp	M24		25.3	48	4.6	4.51
NL1''		1''	27.9	39	3.4	1.53
NL1''sp		1''	27.9	48.5	4.6	4.2
NL27	M27		28.4	42	5.8	3.14
NL27sp	M27		28.4	48.5	5.8	5.27
NL30	M30	11/8''	31.4	47	5.8	4.1
NL30sp	M30	11/8''	31.4	58.5	6.6	8.58
NL33	M33	11/4''	34.4	48.5	5.8	3.89
NL33sp	M33	11/4''	34.4	58.5	6.6	8
NL36	M36	13/8''	37.4	55	5.8	5.49
NL36sp	M36	13/8''	37.4	63	6.6	9.15
NL39	M39	11/2''	40.4	58.5	5.8	5.89
NL42	M42		43.2	63	5.8	7.97
NL45	M45	13/4''	46.2	70	7	10.2
NL48	M48		49.6	75	7	12
NL52	M52	2''	53.6	80	7	13
NL56	M56	21/4''	59.1	85	7	13.5
NL60	M60		63.1	90	7	15.2
NL64	M64	21/2''	67.1	95	7	16.7
NL68	M68		71.1	100	9.5	28.2
NL72	M72		75.1	105	9.5	30.7
NL76	M76	3''	79.1	110	9.5	33.3
NL80	M80		83.1	115	9.5	36
NL85	M85		88.1	120	9.5	37.8
NL90	M90		92.4	130	9.5	47.7
NL95	M95		97.4	135	9.5	49.8
NL100	M100		103.4	145	9.5	58.9
NL105	M105		108.4	150	9.5	61.3
NL110	M110		113.4	155	9.5	63.5
NL115	M115		118.4	165	9.5	75.3
NL120	M120		123.4	170	9.5	77.9
NL125	M125		128.4	173	9.5	76.6
NL130	M130		133.4	178	9.5	79.2



NL3-NL8  
 $Q_i \pm 0.1\text{mm}$   
 NL10-NL42  
 $Q_i \pm 0.2\text{mm}$   
 NL45-NL130  
 $Q_i + 0.5 / - 0\text{mm}$



NL3-NL24  
 $Q_o \pm 0.2\text{mm}$   
 NL27-NL42  
 $Q_o \pm 0.3\text{mm}$   
 NL45-NL130  
 $Q_o + 0 / - 2.0\text{mm}$



NL3-NL27  
 $T \pm 0.25\text{mm}$   
 NL27-NL42  
 $T + 0 / - 0.5\text{mm}$   
 NL45-NL130  
 $T \pm 0.75\text{mm}$

