



单位: mm

d		dc		h		H		
公称直径	max	min	公称	公差	公称	公差	max	min
3	3.35	3.1	6	± 0.24	0.5	± 0.03	0.9	0.7
			8	± 0.29	0.6		1	0.8
			10	± 0.29	0.6		1.2	0.95
4	4.4	4.1	8	± 0.29	0.8	± 0.04	1.2	1
			10	± 0.29	0.9		1.4	1.15
			14	± 0.35	1	± 0.05	1.8	1.4
			10	± 0.29	1		1.6	1.25
5	5.4	5.1	12	± 0.35	1.1	± 0.04	1.8	1.45
			16	± 0.35	1.2		2.1	1.7
6	6.4	6.1	12	± 0.35	1.2	± 0.04	1.85	1.55
			14	± 0.35	1.3		2.1	1.75
			18	± 0.35	1.4	± 0.05	2.5	2.1
			16	± 0.35	1.4		2.2	1.8
8	8.58	8.2	18	± 0.35	1.4	± 0.05	2.35	1.9
			22	± 0.42	1.6		2.7	2.2
10	10.56	10.2	20	± 0.42	1.6	± 0.05	2.6	2.1
			22	± 0.42	1.6		2.75	2.25
			27	± 0.42	1.8	± 0.06	3.1	2.6
			24	± 0.42	1.8		2.9	2.4
12	12.83	12.4	27	± 0.42	1.8	± 0.06	3.1	2.6
			32	± 0.50	2		3.6	3.1
14	14.83	14.4	30	± 0.42	2.4	± 0.06	3.7	3.2
16	16.83	16.4	32	± 0.50	2.8		4.1	3.6
20	21.02	20.5	40	± 0.50	3.2		4.9	4.3